












TECHNICAL CHARACTERISTICS

PURLINE organic flooring | wineo 1000 wood XXL Multi-Layer to click **wineo**
 Long-lasting multi-layer flooring according to ISO 20326 for glueless installation

	wineo 1000 wood XXL Multi-Layer to click
Format	1845 x 237 mm
Product thickness	9 mm
Weight	8.70 kg/m ²
Planks / m² per box	5 / 2.19 m ²
Boxes / m² per pallet	48 / 105.12 m ²
Guarantee	30 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de








Classification		Product composition	
	Utilization class 23 EN ISO 10874	Heavy-duty use in the domestic area	1
	Utilization class 32 EN ISO 10874	Normal use in the commercial sector	
	R9 Anti slip category DIN 51130	R 9	
	Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	2
	Light fastness EN ISO 105-B02	~ 7	3
	Residual indentation EN ISO 24343-1	~ 0.05 mm	4
	Castor chair test EN 425	25000 revolutions no damage with rolls type W	
	Thermal resistance EN 12667	0.06 (m ² K)W	 www.blauer-engel.de/uz176
	Impact sound reduction EN ISO 10140	~ 15 dB	
	Reflected walking sound reduction	~ 29 %	
	REACH	free from SVHC substances ≥ 0.1 %	
	Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	

CE - 18 -

Windmüller GmbH
 Nord-West-Ring 21
 D-32832 Augustdorf


DOP: 0101010
 EN 14041:2004 / AC2006
 1658

E1 $\leq 2 \text{ kV}$ $\geq 0.07 \text{ W/(mK)}$

www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR

 **A+**

A+ A B C

Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

TÜV PROFICERT

70 710 4061-5
www.proficert.com

TFI emissionsgeprüft
 schadstoffgeprüft

PREMIUM

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.